BUTLER TECHNIK | TECHNICAL DOCUMENTATION



E0422MD

Maxus | Deliver 9 Fuel Pickup Instructions

Suitable For the Following Vehicles

Suitable For the Following Heater Kits

Maxus Deliver 9 2020 Onwards

Airtronic S2 D2L

Hydronic S3 HS3 D5E

Autoterm / Planar

Chinese Heaters

Contents	
Description	Quantity
Blue Fuel Line Meter	1
Fuel Hose Small	3
11mm Fuel Hose Clip	6
6 x 4mm straight reducer	1
40mm standpipe adapter	1



NOTE | The Fuel Tank MUST be lowered to access fuel port

Lower the fuel tank to access the fuel sender unit.

The sender unit DOES need to be removed.

Drill an 8mm Hole in the top of the sender unit (Figure 2)

Install standpipe adapter into the 8mm hole and secure using supplied nut.

Secure one of the small equal fuel hose connector to the underside of the standpipe and secure using a clip and then attach a small length of blue fuel line to the other end with another clip, and route over the edge of the sender unit (figure3) secure at bottom using cable tie.

Reinstall the sender unit.

Using another equal fuel hose connector secured with clips, route the remaining blue pipe to the fuel pump and use either the remaining equal fuel hose connector or the supplied reducing hose depending on the outside diameter size of your fuel pump.

It may be Necessary to slightly bend the standpipe as shown in figure4, please ensure the nylon insert is left inside whilst bending to desired angle.

REMOVE Nylon insert before finishing installation.







www.butlertechnik.com 01/12/2022 Version 1.0