

Telestart T99

Simplest way to control Webasto parking heaters remotely



The Telestart T99 is an entry level remote control for all Webasto water heater classes and their sub-versions. The handheld transmitter combines all essential functions in its elegant, compact and portable housing.

The Telestart T99 is made of high quality automotive-grade plastics and chrome plated metal, with elegant design ring holder and complements all types of existing car key fobs. All current Webasto water heaters can be conveniently operated from a range of up to 1,000 m wirelessly.

By default the heater operating time is set for 30 minutes, but with a push of a button it can be individually adjusted between 10 – 120 minutes. Additionally, the continuous operating mode can be switched on, which is exclusive for RV specific water heater versions.

During hot summer days an air ventilation function can be switched on as well, in order to equalize high air temperature inside the vehicle with outside ambient temperature.

Built-in LED informs the user about current status:

- red, static: heating mode selected
- red, blinking: heating is ON
- green, static: ventilation mode selected
- green, blinking: ventilation is ON

The receiver unit, which has to be installed in the vehicle in order to control a parking heater, can now be operated by up to 4 different Telestart T99 remote controls, which is convenient for larger families or several drivers of one single vehicle.

Key benefits at a glance:

- Modern and timeless design
- Up to 1,000 meters range
- Select heating time over distance
- Switch between winter heating and summer air ventilation modes
- Multi-colored LED for status report
- One remote control for different vehicle types
- Up to four remote controls per vehicle possible with family function
- Supports all current Webasto water heater classes and versions

As advised by Webasto: Webasto Air Top Heaters are also supported when installed with a Webasto MultiControl (Part No.9030910A)



Car


Light
vehicles

Recreational
vehicles


Marine

Technical specifications

	Transmitter	Receiver
Operating time	10 – 120 minutes Adjustable in 10 minutes increments Continuous heating function (RV only)	
Operating distance (m)	Up to 1,000	—
Radio frequency (Mhz)	869.0 (proprietary)	
Power supply	Battery CR 2032 3V	12V DC
Operating temperature range (C°)	0 to +50	-40 to +85
Dimensions L x W x H (mm)	61.8 x 32.9 x 13.9	92 x 64 x 24.2
Weight (g)	32 (including battery)	66
IP protection class	IP 44	IP 42
Connection type	—	Analog switch output / WBus
ECE approval number	E1 10R - 059049	
CE declaration of conformity	2014/53/EU for further information see declaration of conformity	

Scope of delivery:

- Transmitter Telestart T99 (battery included)
- Receiver Telestart T99
- Wiring harness
- Window antenna
- Mounting bracket for receiver
- QuickStart Guide

Supported Webasto heaters:

- Thermo Top Evo 4 / 5 / 5+
- Thermo Pro 90 (12 V variant only)
- Thermo Top Pro 120 / 150 (12 V variant only)

Accessories:

- Toggle ON / OFF button for dashboard installation

UNCONTROLLED
COPY



Contact details